



OPTIONALS



- KIT TENDITORI DI FISSAGGIO
- ALBERO CARDANICO
- TRACTOR STABILIZERS
- P.T.O. DRIVE SHAFTS
- SPANNHALTER ZUM SCHLEPPER
- GELENKWELLEN
- TENDEURS RÉGLABLE
- CARDAN
- KIT TENSORES DE FIJACIÓN
- ÁRBOL CÁRDAN



- SCAMBIATORE DI CALORE
- HEAT EXCHANGER
- WÄRMEAUSTAUSCHER
- ÉCHANGEUR DE CHALEUR
- REFRIGERADOR




- COMANDO ELETTROIDRAULICO CON JOYSTICK
- ELECTRIC CONTROL JOYSTICK
- ELEKTROHYDRAULISCHE STEUERUNG MIT JOYSTICK
- COMMANDE ÉLECTROHYDRAULIQUE MONO-LEVIER
- MANDO ELECTRO-HIDRÁULICO CON «JOYSTICK»



- SUPPORTO TERZO PUNTO
- SUPPORT STRETCHERS
- TRÄGER SPANNVORRICHTUNG
- SUPPORT TENDEURS
- SOPORTE TIRANTES



Serie G



- ROTAZIONE IDRAULICA CON DISPOSITIVO OLEODINAMICO DI SICUREZZA
- HYDRAULIC ROTATION WITH HYDRAULIC SAFETY DEVICE
- HYDRAULISCHE ROTATION MIT HYDRAULISCHER SICHERHEITSVORRICHTUNG
- DISPOSITIF HYDRAULIQUE DE SÛRETÉ
- ROTACIÓN HIDRÁULICA CON DISPOSITIVO HIDRÁULICO DE SEGURIDAD



DATI TECNICI / SPECIFICATIONS TECHNISCHE DATEN / CARACTÉRISTIQUES / DATOS TÉCNICOS					
MOVIMENTAZIONE BRACCI / ARM MOTION BEWEGUNG ARME / MOUVEMENT DES BRAS / MOVIMIENTO BRAZOS				DEC 300 G	DEC 380 G
A	(mm.)	A	(mm.)	1400	1600
B	(mm.)	B	(mm.)	3000	3800
C	(mm.)	C	(mm.)	1200	1200
D	(mm.)	D	(mm.)	3200	4000
E	(mm.)	E	(mm.)	1600	2200
Peso Standard Weight - Gewicht	(kg.)	Poids Peso	(kg.)	380	400
IMPIANTO IDRAULICO / HYDRAULIC SYSTEM HYDRAULISCHE ANLAGE / INSTALLATION HYDRAULIQUE / INSTALACIÓN HIDRÁULICA				DEC 300 G	DEC 380 G
Capacità serbatoio olio Oil tank capacity - Fassungsvermögen Öltank	(lt)	Capacité réservoir huile Capacidad depósito aceite	(lt)	80	
Oilio idraulico Hydraulic oil - Hydraulisches Öl	(tipo)	Huile hydraulique Aceite hidráulico	(tipo)	ISO - L - HM 68	
TESTATA / HEAD MULCHKOPF / TÊTE / CABEZAL TRITURADOR				DEC 300 G	DEC 380 G
G- larghezza di lavoro G- Working width - F- Weite Arbeitsbereich	(mm.)	G- Largeur de travail G- ancho de trabajo	(mm.)	600	800
Peso Weight - Gewicht	(kg.)	Poids Peso	(kg.)	70	100
Velocità rotore Rotor speed - Rotorschwindigkeit	(giri/min.)	Vitesse rotor Velocidad del rotor	(giri/min.)	2800	2800
Potenza rotore Rotor power - Rotorleistung	HP	Puissance rotor Potencia del rotor	HP	29	
TRATTORE / TRACTOR TRAKTOREN / TRACTEUR / TRACTOR				DEC 300 G	DEC 380 G
Potenza minima Min. power requirements - Mindestleistung	(HP)	Puissance min. requise Potencia mínima	(HP)	30	35
Peso minimo Min. weight - Mindestgewicht	(kg.)	Poids min. Peso mínimo	(kg.)	1600	2000
Velocità presa di forza Pto speed - Zapflwellendrehzahl	(RPM)	Vitesse Pdf Velocidad toma de fuerza	(RPM)	540	540